

**PATENT ABSTRACTS OF JAPAN**

(11)Publication number : **11-100243**  
(43)Date of publication of application : **13.04.1999**

---

(51)Int.Cl.

C04B 7/38  
B09B 3/00  
C04B 7/60

---

(21)Application number : **10-156202**  
(22)Date of filing : **04.06.1998**

(71)Applicant : **TAIHEIYO CEMENT CORP**  
(72)Inventor : **ITO MITSUHIRO**  
**HIROSE TOSHIAKI**  
**TAKAHASHI HIROAKI**

---

(30)Priority

Priority number : **09205246** Priority date : **14.07.1997** Priority country : **JP**

---

**(54) CONVERSION TREATMENT OF WASTE INTO CEMENT RAW MATERIAL**

(57)Abstract:

**PROBLEM TO BE SOLVED:** To effectively utilize waste conventionally subjected to landfill disposal by using as a cement raw material, desalted cake obtained with the treatment that comprises adding water to waste contg. chlorine to elute chlorine in the waste, and filtering the resulting material.  
**SOLUTION:** This treatment is used for treating as waste contg. chlorine, preferably, fly ash discharged at the time of incinerating waste, or dust formed by a process that comprises: circulating volatile components such as chlorine, sulfur and alkali, through a cement kiln and a preheater in a cement production equipment to concentrate them; then, extracting the volatile components together with an exhaust gas out of the kiln; quenching the extracted exhaust gas contg. the components such as chlorine, sulfur and alkali, at a temp. equal to or lower than the melting points of the compounds of these components; and thereafter, removing the components as dust contg. water-soluble chlorine compounds. The treatment comprises: adding water to such waste contg. chlorine to elute chlorine in the waste; filtering the resulting material to separate a filtrate and to obtain the objective desalted cake which is used as cement raw material; precipitating heavy metals and hazardous substances in the filtrate to remove the heavy metals and hazardous substances by filtration; evaporating the filtrate thus obtained to separate and remove chlorides as the evaporation residue; and on the other hand, the evaporated water is liquefied to obtain water which is preferably reused for eluting chlorine.

---

**LEGAL STATUS**

[Date of request for examination] 08.11.1999

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]	3304300
[Date of registration]	10.05.2002
[Number of appeal against examiner's decision of rejection]	
[Date of requesting appeal against examiner's decision of rejection]	
[Date of extinction of right]	

Copyright (C); 1998,2003 Japan Patent Office